

## CERTIFICATE OF COMPLIANCE

### WIND RESISTANT DESIGN OF NONSTRUCTURAL COMPONENTS AND SYSTEMS



Certification No.

**VMA-54559-01C (Revision 0)**

Expiration Date: 09/30/2028

#### Certification Parameters:

The nonstructural products containing non-active components, listed on this certificate are CERTIFIED<sup>1</sup> FOR WIND APPLICATIONS in accordance with the following building code<sup>3</sup> releases.

#### IBC 2021, 2018

The following model designations, options, and accessories are included in this certification. Reference report number **VMA-54559-01** as issued by VMC Group for a complete list of certified models, included accessories/options, and certified installation methods.

#### Cummins; DSHAD & DQDAx Enclosures Horizontal & Vertical Discharge Aluminum Enclosures; SL2 & Weather

The above referenced non-active components equipment is **APPROVED** for wind application when properly installed<sup>2</sup>, used as intended, and contains a Wind Certification Label referencing this Certificate of Compliance. Installations in essential facilities, for life safety applications, and/or of equipment containing hazardous contents are permitted and included in this certification with an Equipment Importance Factor assigned as  $I_p=1.15$ . The equipment is qualified by ISO Accredited Product Certification Agency, VMC Group via structural analysis of worst-case representative sample of certified product.

Certified Wind Resistant Design Levels			
Certified IBC	Importance $I_p \leq 1.15$ Exposure Categories A-D Risk Categories I-IV	$V \leq 120$ mph $V \leq 53$ m/s	$V \leq 120$ mph $V \leq 53$ m/s
		$z \leq 15$ ft $z \leq 5$ m	$z \leq 500$ ft $z \leq 152$ m
		Pressure Basis <sup>4</sup>	$\frac{F_h}{A_f} = q_z G C_f =$ <b>50.61 lbs/ft<sup>2</sup></b> 2.42 kPa

Certified Wind Resistant Installation Methods
Rigid Mounting From Unit Base to Rigid Structure

HEADQUARTERS/New Jersey | 113 Main St., Bloomington, NJ 07403 | 973.838.1780 | 800.569.8423 | [thevmcgroup.com](http://thevmcgroup.com)

**FABRICATION/Texas**  
11930 Brittmoore Park Dr.  
Houston, TX 77041  
713.466.0003  
800.569.8423

**CANFAB/California**  
182 Granite St., Suite 101  
Corona, CA 92879  
800.232.2632  
[canfab.com](http://canfab.com)

**BRD/Pennsylvania**  
112 Fairview Ave.  
Wind Gap, PA 18091  
610.863.6300  
[hushcore.net](http://hushcore.net)

**DCL/Nevada**  
1315 Greg St., Suite 109  
Sparks, NV 89431  
775.358.5085  
[shaketest.com](http://shaketest.com)

## CERTIFICATE OF COMPLIANCE

### WIND RESISTANT DESIGN OF NONSTRUCTURAL COMPONENTS AND SYSTEMS

**Certified Product Table:**

Applicable Genset	Model ( Feature Code )	Type	Material	Dimensions [ in ]			Weight ( lbs )	Wind Velocity @ Z ≤ 15 ft Exposure Category C
				Length	Width	Height		
DSHAD ( QSL9-G2 ) DQDAx ( QSL9-G7 )	Horizontal Discharge ( F282-2 )	SL2, Weather	Aluminum	183	57	86	2,112	120mph
		SL2		204	57	86	2,293	
	Vertical Discharge ( F252-2 )	SL2, Weather		183	57	86	2,430	
		SL2		204	57	86	2,575	

IBC		2021, 2018		
ASCE		7-16		
Exposure Category		B	C	D
Velocity <sup>5</sup> (mph)	Z ≤ 15 ft	146	120	109
	Z = 200 ft	100	91	87
	Z ≤ 500 ft	88	83	80



VMA- 54559-01C (Revision 0)  
 Issue Date: September 11, 2025  
 Revision Date: September 11, 2025  
**Expiration Date: September 30, 2028**

**HEADQUARTERS/New Jersey** | 113 Main St., Bloomingdale, NJ 07403 | 973.838.1780 | 800.569.8423 | [thevmcgroup.com](http://thevmcgroup.com)

**FABRICATION/Texas**  
 11930 Brittmoore Park Dr.  
 Houston, TX 77041  
 713.466.0003  
 800.569.8423

**CANFAB/California**  
 182 Granite St., Suite 101  
 Corona, CA 92879  
 800.232.2632  
[canfab.com](http://canfab.com)

**BRD/Pennsylvania**  
 112 Fairview Ave.  
 Wind Gap, PA 18091  
 610.863.6300  
[hushcore.net](http://hushcore.net)

**DCL/Nevada**  
 1315 Greg St., Suite 109  
 Sparks, NV 89431  
 775.358.5085  
[shaketest.com](http://shaketest.com)

## CERTIFICATE OF COMPLIANCE

### WIND RESISTANT DESIGN OF NONSTRUCTURAL COMPONENTS AND SYSTEMS

**Notes and Comments:**

1. The following building codes are addressed under this certification:
  - IBC 2021 – referencing ASCE 7-16
  - IBC 2018 – referencing ASCE 7-16
2. Refer to the manufacturer supplied installation drawings for anchor requirements and mounting considerations for wind applications. Required anchor locations, size, style, and load capacities (tension and shear) are specified on the installation drawings. Mounting requirement details such as anchor brand, type, embedment depth, edge spacing, anchor-to-anchor spacing, concrete strength, special inspection, wall design, and attachment to non-building structures must be outlined and approved by the Engineer of Record for the project or building. Structural walls, structural floors, and housekeeping pads must also be sufficiently designed and approved by the project or building Structural Engineer of Record to withstand the wind anchor loads as defined on the installation drawings. The installing contractor is responsible for observing the installation detailed in the wind installation drawings and the proper installation of all anchors and mounting hardware.
3. For this certificate to remain valid, it must correspond to the "Wind Certification Label" found affixed to the unit by the factory. The label ensures the manufacturer built the unit in conformance to the IBC wind design criteria set forth by the Product Certification Agency, The VMC Group, and meets the wind design levels claimed by this certificate.
4. The qualified wind design pressure stated is for the horizontal wind pressure for applications utilizing ASCE 7-16, for more detailed ranges of qualified wind design levels, sees the report cited on Page 1. This wind design pressure utilizes LRFD load combinations.
5. Design velocity (highlighted in yellow) was chosen based on the corresponding ASCE 7 wind map. Other velocities were derived from the design pressure resulting from the design velocity.
6. Mechanical, Electrical, and Plumbing connections to the equipment must be flexibly attached as to not transfer load through the connection. The structural integrity of any conduit, cable trays, piping, ductwork and/or flexible connections is the responsibility of others. This certification does not guarantee the equipment will remain compliant to UL or NEMA standards after a wind action.
7. This certificate applies to units manufactured at
  - Cummins Power Generation, Inc, 1400 73<sup>rd</sup> Ave NE, Minneapolis, MN 55432
8. This project follows VMC Group's ISO-17065 Scheme for Product Certification of Nonstructural Components.

  
 John P. Giuliano, PE  
 President, The VMC Group



VMA-54559-01C (Revision 0)  
 Issue Date: September 11, 2025  
 Revision Date: September 11, 2025  
**Expiration Date: September 30, 2028**



**HEADQUARTERS/New Jersey** | 113 Main St., Bloomington, NJ 07403 | 973.838.1780 | 800.569.8423 | [thevmcgroup.com](http://thevmcgroup.com)

**FABRICATION/Texas**  
 11930 Brittmoore Park Dr.  
 Houston, TX 77041  
 713.466.0003  
 800.569.8423

**CANFAB/California**  
 182 Granite St., Suite 101  
 Corona, CA 92879  
 800.232.2632  
[canfab.com](http://canfab.com)

**BRD/Pennsylvania**  
 112 Fairview Ave.  
 Wind Gap, PA 18091  
 610.863.6300  
[hushcore.net](http://hushcore.net)

**DCL/Nevada**  
 1315 Greg St., Suite 109  
 Sparks, NV 89431  
 775.358.5085  
[shaketest.com](http://shaketest.com)